



MARK	REVISION RECORD	DATE	REVISED BY	CHKD. BY	APPD.
△					
△					
△					
△					

PARTS QTY. NO.	PARTS NAME	MATERIAL	TREAT.	DIMENSION	WEIGHT
				MTL.	FINED.
1	01	EVAPORATOR		MULTI-PASS CROSS FINNED TUBE	
2	02	EXPANSION V/V		TDEX16 OR EQUIV.	
2	03	HEADER		φ35	
2	04	DISTRIBUTER		φ58	
2	05	FILTER DRYER		3/4"	
1	06	BLOWER MOTOR		AC 3φ V 60Hz 4P 3.7kW	
1	07	MOTOR PULLEY		2B 5"	
2	08	V-BELT	RUBBER	#B	
2	09	BLOWER		DS #2-1/2	
1	10	BLOWER PULLEY		2B 9.5"	
1	11	SHAFT		ASS'Y	
2	12	BEARING		ASS'Y	
2	13	HIGH PRESSURE GAUGE		-0.1~3.5 MPa	
2	14	LOW PRESSURE GAUGE		-0.1~1.5 MPa	
1	15	SWITCH BOX		ASS'Y	
1	16	CONTROL BOX		ASS'Y	
1	17	AIR FILTER		ASS'Y	
1	18	AIR INLET		ASS'Y	
1	19	AIR OUTLET		ASS'Y	
2	20	HUMIDIFIER		ASS'Y	
1	21	HEATING COIL(EHC)		60kW	

SPECIFICATIONS

ITEM	UNIT	MODEL
COOLING CAPACITY	kcal/h	HT-A30GG3 84,000
NOMINAL AIR VOLUME	CMM	260
EXTERNAL STATIC PRESSURE	mmAq	0
HEATING CAPACITY	kcal/h	51,600
AUX. HEATER	STEAM	kg/cm ² G ROW
	HOT WATER	°C ROW
	ELECTRIC	60 kW
HUMIDIFIER	HUMIDIFIER CAPACITY	kg/h 16 kg/h
	STEAM	kg/cm ² G
	HOT WATER	kg/cm ² G
PIPING	CONNECTION DIRECTION	GAS&LIQUID RIGHT (LEFT)
	HEATING	RIGHT LEFT
	HUMIDIFIER	RIGHT LEFT
	CONNECTION SIZE	GAS&LIQUID GAS 1-3/8" LIQUID 3/4"
	FOR HEATING	INLET A OUTLET A
STANDARD CONDITION	INDOOR	25°C ± 2°C, 55% ± 5% RH
	OUTDOOR	35°C DB

- NOTE.
1. STANDARD PIPING DIRECTION IS LEFT.
 2. PAINTING COLOR : MUNSELL NO. 5Y 6.5/1)
 3. OUTDOOR UNIT : RC-F15G7 x 2UNIT

TOLERANCES UNLESS OTHERWISE SPECIFIED		TITLE	
PRODUCT NAME	COMPUTER ROOM PACKAGE AIR CONDITIONER	ASSEMBLY DWG.	
MODEL	HT-A30GG3	(AIR COOLED TYPE)	
DWN. BY	DESIGNED BY	CHKD. BY	APPD.
THIRD ANGLE PROJECTION		SCALE 1:18	UNIT : mm
REFERENCE			
DRAWING NO.		HTU300-13120GG	



(주)세원센추리